

UNSTOPPABLE



CUTTERS

MEET THE ONLY BATTERY-POWERED, UNDERWATER CUTTING TOOLS. NO WONDER THEY ARE JAWS.

These rescue tools are the first of their kind, allowing you to operate submerged in freshwater and unencumbered by any hoses or power units. And despite this unique skill, they are still some of the fastest, most powerful cutters in the business.

Features and Benefits:

- Watertight, allows you to operate the tool submerged in fresh water
- Brushless DC electrical motor runs more efficiently with higher performance for a longer battery life
- Two LED lights illuminate the front of the tool
- Large waterproof 9Ah battery with IP68 protection class
- Ergonomically designed star-grip permits tool actuation from almost any gripping position
- 4-stage heat treated shock resistant blades
- Advanced blade design
- UHSS capable
- One piece body construction
- Cutting edge of blade can be resurfaced



CUTTERS



S 378 EWXT

272278000-1 (Tool Only)

272278000-5 (includes tool, (2) 5Ah batteries and (1) charger)
272278000-9 (includes tool, (2) 9Ah batteries and (1) charger)



S 788 EWXT

272288000-1 (Tool Only)

272288000-5 (includes tool, (2) 5Ah batteries and (1) charger)
272288000-9 (includes tool, (2) 9Ah batteries and (1) charger)



S 789 EWXT

272289000-1 (Tool Only)

272289000-5 (includes tool, (2) 5Ah batteries and (1) charger)
272289000-9 (includes tool, (2) 9Ah batteries and (1) charger)



S 799 EWXT

272299000-1 (Tool Only)

272299000-5 (includes tool, (2) 5Ah batteries and (1) charger)
272299000-9 (includes tool, (2) 9Ah batteries and (1) charger)

TECHNICAL SPECIFICATIONS

- Length (w/o battery): 33.3 in / 846 mm
- Width: 9.25 in / 235 mm
- Height (w/o battery): 9.96 in / 253 mm
- Weight (w/o battery): 40.8 lbs / 18.5 kg
- Cutter Opening: 7.99 in / 202 mm
- NFPA Cutter Rating: A7/B8/C7/D7/E8
- NFPA 1936 2020 Compliant: Pending
- Tool IP Rating: IP58
- Battery IP Rating: IP68

TECHNICAL SPECIFICATIONS

- Length (w/o battery): 35.6 in / 904 mm
- Width: 10.5 in / 266 mm
- Height (w/o battery): 9.96 in / 253 mm
- Weight (w/o battery): 48.9 lbs / 22.2 kg
- Cutter Opening: 7.87 in / 200 mm
- NFPA Cutter Rating: A8/B9/C8/D9/E9/F4
- NFPA 1936 2020 Compliant: Yes
- Tool IP Rating: IP58
- Battery IP Rating: IP68

TECHNICAL SPECIFICATIONS

- Length (w/o battery): 35.9 in / 912 mm
- Width: 10.5 in / 266 mm
- Height (w/o battery): 9.96 in / 253 mm
- Weight (w/o battery): 49.4 lbs / 22.4 kg
- Cutter Opening: 8.06 in / 205 mm
- NFPA Cutter Rating: A8/B9/C8/D9/E9/F5
- NFPA 1936 2020 Compliant: Yes
- Tool IP Rating: IP58
- Battery IP Rating: IP68

TECHNICAL SPECIFICATIONS

- Length (w/o battery): 36.6 in / 930 mm
- Width: 10.4 in / 265 mm
- Height (w/o battery): 9.96 in / 253 mm
- Weight (w/o battery): 54.9 lbs / 24.9 kg
- Cutter Opening: 8.03 in / 204 mm
- NFPA Cutter Rating: A9/B9/C9/D9/E9/F5
- NFPA 1936 2020 Compliant: Yes
- Tool IP Rating: IP58
- Battery IP Rating: IP68

UNSTOPPABLE



SPREADERS

GREAT FOR MAKING UNDERWATER EXITS.

HURST Jaws of Life EWXT spreaders are game-changers. They are the first of their kind and allow you to operate submerged in fresh water and unencumbered by any hoses or power units. And despite all that, they are still some of the lightest, most powerful spreaders in the business. The water is a lot safer now.

Features and Benefits:

- Watertight, allows you to operate the tool submerged in fresh water
- Squeezing plates built into the arms
- “Shark Tooth” removable tips offer multifunctional design, with four rows of shark-like teeth designed to grab and maintain position on UHSS structures and panels for both spreading and crushing applications
- Brushless DC electrical motor runs more efficiently with higher performance for a longer battery life
- Quieter
- Two LED lights illuminate the front of the tool
- Ergonomically designed star-grip permits tool actuation from almost any gripping position
- Large waterproof 9Ah battery with IP68 protection class
- Lightweight design
- One piece body construction
- Accessories such as pulling chains and stability plate attach through tip pin hole for quick deployment



SPREADERS



SP 333 EWXT

271233000-1 (Tool Only)

271233000-5 (includes tool, (2) 5Ah batteries and (1) charger)
271233000-9 (includes tool, (2) 9Ah batteries and (1) charger)



SP 555 EWXT

271255000-1 (Tool Only)

271255000-5 (includes tool, (2) 5Ah batteries and (1) charger)
271255000-9 (includes tool, (2) 9Ah batteries and (1) charger)



SP 777 EWXT

271277000-1 (Tool Only)

271277000-5 (includes tool, (2) 5Ah batteries and (1) charger)
271277000-9 (includes tool, (2) 9Ah batteries and (1) charger)

TECHNICAL SPECIFICATIONS

- Length (w/o battery): 32.4 in / 823 mm
- Width: 10.1 in / 256 mm
- Height (w/o battery): 9.96 in / 253 mm
- Weight (w/o battery): 37.7 lbs / 17.1 kg
- Spreading Distance: 23.6 in / 600 mm
- Maximum Spreading Force: 187,940 Lbf / 836 kN
- Maximum Pulling Force: 12,589 Lbf / 56 kN
- NFPA HSF: 14,162 Lbf / 63 kN
- NFPA LSF: 8,768 Lbf / 39 kN
- NFPA HPF: 9,667 Lbf / 43 kN
- NFPA LPF: 5,171 Lbf / 23 kN
- NFPA 1936 2020 Compliant: Yes
- Tool IP Rating: IP58
- Battery IP Rating: IP68

TECHNICAL SPECIFICATIONS

- Length (w/o battery): 36.3 in / 923 mm
- Width: 10.4 in / 265 mm
- Height (w/o battery): 9.96 in / 253 mm
- Weight (w/o battery): 43.9 lbs / 19.9 kg
- Spreading Distance: 28.7 in / 730 mm
- Maximum Spreading Force: 147,924 Lbf / 658 kN
- Maximum Pulling Force: 13,039 Lbf / 58 kN
- NFPA HSF: 16,186 Lbf / 72 kN
- NFPA LSF: 11,016 Lbf / 49 kN
- NFPA HPF: 10,341 Lbf / 46 kN
- NFPA LPF: 6,295 Lbf / 28 kN
- NFPA 1936 2020 Compliant: Yes
- Tool IP Rating: IP58
- Battery IP Rating: IP68

TECHNICAL SPECIFICATIONS

- Length (w/o battery): 39.3 in / 997 mm
- Width: 12.2 in / 309 mm
- Height (w/o battery): 9.96 in / 253 mm
- Weight (w/o battery): 51.6 lbs / 23.4 kg
- Spreading Distance: 32 in / 813 mm
- Maximum Spreading Force: 134,900 Lbf / 600 kN
- Maximum Pulling Force: 13,490 Lbf / 60 kN
- NFPA HSF: 19,110 Lbf / 85 kN
- NFPA LSF: 13,260 Lbf / 59 kN
- NFPA HPF: 11,016 Lbf / 49 kN
- NFPA LPF: 6,774 Lbf / 30 kN
- NFPA 1936 2020 Compliant: Yes
- Tool IP Rating: IP58
- Battery IP Rating: IP68

UNSTOPPABLE



RAMS

PACKS AN UNDERWATER PUNCH.

What they do above water is incredible. What they do underwater is downright absurd. These rams are the first of their kind, allowing you to create wide opening for rescue while submerged in fresh water without being encumbered by any hoses or power units. The sharp claws at both ends enable you to apply it effectively in almost any precarious situation — especially underwater.

Features and Benefits:

- Watertight, allows you to operate the tool submerged in fresh water
- Brushless DC electrical motor runs more efficiently with higher performance for a longer battery life
- Four LED lights illuminate the front and back of the tool
- Large waterproof 9Ah battery with IP68 protection class
- Ergonomically designed star-grip permits tool actuation from almost any gripping position
- Rotating claw heads allow for better patient access
- Telescoping design allows for minimal insertion and maximum spread
- Great for forcible entry as well



RAMS



R 521 EWXT

274285000-1 (Tool Only)

274285000-5 (includes tool, (2) 5Ah batteries and (1) charger)
274285000-9 (includes tool, (2) 9Ah batteries and (1) charger)



R 522 EWXT

274286000-1 (Tool Only)

274286000-5 (includes tool, (2) 5Ah batteries and (1) charger)
274286000-9 (includes tool, (2) 9Ah batteries and (1) charger)

TECHNICAL SPECIFICATIONS

- Length (w/o battery): 22.8 in / 579 mm
- Length Extended (w/o battery): 53.5 in / 1359 mm
- Width: 5.51 in / 140 mm
- Height (w/o battery): 12.9 in / 327 mm
- Weight (w/o battery): 41.9 lbs / 19 kg
- Stroke Piston 1: 15.6 in / 403 mm
- HSF Piston 1: 28,600 Lbf / 127 kN
- Stroke Piston 2: 14.8 in / 377 mm
- HSF Piston 2: 13,500 Lbf / 60 kN
- Stroke Overall: 30.7 in / 780 mm
- NFPA 1936 2020 Compliant: Yes
- Tool IP Rating: IP58
- Battery IP Rating: IP68

TECHNICAL SPECIFICATIONS

- Length (w/o battery): 24.7 in / 627 mm
- Length Extended (w/o battery): 59.2 in / 1503 mm
- Width: 5.51 in / 140 mm
- Height (w/o battery): 12.9 in / 327 mm
- Weight (w/o battery): 44.8 lbs / 20.3 kg
- Stroke Piston 1: 17.8 in / 451 mm
- HSF Piston 1: 28,600 Lbf / 127 kN
- Stroke Piston 2: 16.7 in / 425 mm
- HSF Piston 2: 13,500 Lbf / 60 kN
- Stroke Overall: 34.5 in / 876 mm
- NFPA 1936 2020 Compliant: Yes
- Tool IP Rating: IP58
- Battery IP Rating: IP68

UNSTOPPABLE



COMBI TOOLS

SAVE LIVES QUICKLY, AND WHEREVER YOU'RE NEEDED

First responders need to be ready for everything. This tool can help them accomplish that. It spreads, it cuts, it doesn't need hoses or power units, and it even works submerged in water.

Features and Benefits:

- Watertight, allows you to operate the tool submerged in fresh water
- Brushless DC electrical motor runs more efficiently with higher performance for a longer battery life
- Two LED lights illuminate the front of the tool
- Large waterproof 9Ah battery with IP68 protection class
- Ergonomically designed star-grip permits tool actuation from almost any gripping position
- 4-stage heat treated shock resistance blades
- Removable Shark tooth tips with self-retaining pin (SC 358/758 EWXT only)
- Removable tips to allow for deeper cuts when needed (SC 358/758 EWXT only)
- One piece body construction
- Accessories such as pulling chains and stability plate attach through tip pin hole for quick deployment
- Great for forcible entry and RIT as well as standard extrication needs



COMBI TOOLS



SC 258 EWXT

273228000-1 (Tool Only)

273228000-5 (includes tool, (2) 5Ah batteries and (1) charger)
273228000-9 (includes tool, (2) 9Ah batteries and (1) charger)



SC 358 EWXT

273223000-1 (Tool Only)

273223000-5 (includes tool, (2) 5Ah batteries and (1) charger)
273223000-9 (includes tool, (2) 9Ah batteries and (1) charger)



SC 758 EWXT

273249000-1 (Tool Only)

273249000-5 (includes tool, (2) 5Ah batteries and (1) charger)
273249000-9 (includes tool, (2) 9Ah batteries and (1) charger)

TECHNICAL SPECIFICATIONS

- Length (w/o battery): 31.2 in / 792 mm
- Width: 8.27 in / 210 mm
- Height (w/o battery): 9.96 in / 253 mm
- Weight (w/o battery): 31.7 lbs / 14.4 kg
- Spreading Distance: 12.6 in / 321 mm
- Maximum Spreading Force: 157,000 Lbf / 700 kN
- Maximum Pulling Force: 7,640 Lbf / 34 kN
- Cutter Opening: 9.2 in / 233 mm
- NFPA Cutter Rating: A6/B6/C6/D7/E7/F4
- NFPA HSF: 6,500 Lbf / 29 kN
- NFPA LSF: 5,400 Lbf / 24 kN
- NFPA HPF: 8,320 Lbf / 37 kN
- NFPA LPF: 6,300 Lbf / 28 kN
- NFPA 1936 2020 Compliant: Yes
- Tool IP Rating: IP58
- Battery IP Rating: IP68

TECHNICAL SPECIFICATIONS

- Length (w/o battery): 34.5 in / 876 mm
- Width: 9.25 in / 235 mm
- Height (w/o battery): 9.96 in / 253 mm
- Weight (w/o battery): 40.6 lbs / 18.4 kg
- Spreading Distance: 14.5 in / 368 mm
- Maximum Spreading Force: 337,230 Lbf / 1500 kN
- Maximum Pulling Force: 13,714 Lbf / 61 kN
- Cutter Opening: 12.2 in / 309 mm
- NFPA Cutter Rating: A7/B8/C7/D8/E7/F4
- NFPA HSF: 6,667 Lbf / 43 kN
- NFPA LSF: 7,419 Lbf / 33 kN
- NFPA HPF: 13,940 Lbf / 62 kN
- NFPA LPF: 9,667 Lbf / 43 kN
- NFPA 1936 2020 Compliant: Yes
- Tool IP Rating: IP58
- Battery IP Rating: IP68

TECHNICAL SPECIFICATIONS

- Length (w/o battery): 38.6 in / 950 mm
- Width: 10.5 in / 266 mm
- Height (w/o battery): 9.96 in / 253 mm
- Weight (w/o battery): 52.9 lbs / 24 kg
- Spreading Distance: 18.7 in / 475 mm
- Maximum Spreading Force: 337,213 Lbf / 1500 kN
- Maximum Pulling Force: 21,132 Lbf / 94 kN
- Cutter Opening: 15.7 in / 400 mm
- NFPA Cutter Rating: A8/B9/C9/D9/E9/F5
- NFPA HSF: 11,016 Lbf / 49 kN
- NFPA LSF: 8,543 Lbf / 38 kN
- NFPA HPF: 15,512 Lbf / 69 kN
- NFPA LPF: 11,690 Lbf / 52 kN
- NFPA 1936 2020 Compliant: Yes
- Tool IP Rating: IP58
- Battery IP Rating: IP68